



# HP MSM-802.11n Access Point Series



## Key features

- Single radio IEEE 802.11 a/b/g/n access point
- Capability to work with wireless controller and in autonomous mode
- Comprehensive WLAN security
- Protection against rogue IEEE 802.11a/b/g/n access points and client
- Indoor enclosure

## Product overview

HP offers intelligent IEEE 802.11n wireless access points, ranging from our single-radio 802.11a/b/g/n to our dual 802.11a/b/g/n access points. The MSM access points are advanced wireless devices that provide consistent, easy-to-manage connectivity that expands your existing network. The access points maintain your network without interruption and reduce bottlenecks and network complexity by determining where data needs to go throughout the network. The MSM access points provide complete wireless coverage for greater reliability and connectivity and can be used in managed mode as well as autonomous mode without a controller.

Working in unison with HP MSM controllers, the HP MSM-802.11n Access Point Series delivers high-performance networking solutions. The enhanced controller architecture scales to IEEE 802.11n without requiring a controller replacement. The MSM controller provides advanced radio resource management (RRM), including client load balancing and interference mitigation. The MSM wireless controllers

support a fast-roaming capability, a feature that is especially for VoIP communications.

Wireless security is comprehensive with integrated Wireless IDS and support for internal and external authentication, authorization, and accounting (AAA) servers; built-in stateful firewall; per-user VLAN mapping; and authentication.

## Features and benefits

### Management

- **Wi-Fi Clear Connect**  
provides a system-wide approach to improve WLAN reliability by proactively determining and adjusting to changing RF conditions; helps optimize WLAN performance by identifying rogue activity and making decisions at a system-wide level
- **Advanced radio resource management**
  - **Automatic radio power adjustments**  
include real-time power adjustments based on changing environmental conditions and signal coverage adjustments
  - **Automatic radio channel**  
provides intelligent channel switching and real-time Interference detection
  - **Intelligent client load balancing**  
determines the number of clients across neighboring APs and adjusts client allocation to balance the load
  - **Airtime fairness**  
provides equal RF transmission time for wireless clients
- **Integrated IDS (Premium Mobility version required)**
  - detects and locates unknown and rogue devices
- **Access point management**  
provides secure Web browser (SSL, VPN), command-line interface, SNMP v2c, SNMP v3, MIB-II with traps, and RADIUS Authentication Client MIB (RFC 2618); offers embedded HTML management tool with secure access (SSL and VPN); implements scheduled configuration and firmware upgrades from a central controller
- **HP Intelligent Management Center and Wireless Services Manager Software**  
provides central management for discovery, logging, status, and configuration management
- **Diagnostics**  
client event log records association, authentication, and DHCP events; packet capture tool for Ethernet and IEEE 802.11 interfaces (PCAP format); data rate matrix
- **Enhanced AP survivability**  
continues to operate using the old IP address while the AP searches for a new controller

### Quality of Service (QoS)

- **Rate limiting**  
supports per-wireless client ingress-enforced maximums and per-wireless client, per-queue guaranteed minimums
- **Centralized traffic**  
Layer 2 and Layer 3 QoS settings are maintained when using Mobility Traffic Manager or guest access
- **IEEE 802.1p prioritization**  
delivers data to devices based on the priority and type of traffic

### Wireless

- **L2/L3/L4 classification**  
IEEE 802.1p VLAN priority, SpectraLink SVP, and DiffServ
- **Assigned by VSC**  
Wi-Fi MultiMedia (WMM), IEEE 802.11e EDCF, and Service-Aware priority
- **Maximum VoIP call capacity**  
12 active calls on IEEE 802.11 a/b/g/n
- **SpectraLink Voice Priority (SVP) support**  
prioritizes SpectraLink voice IP packets sent from a SpectraLink NetLink SVP server to SpectraLink wireless voice handsets to help ensure excellent voice quality

### Connectivity

- **IEEE 802.3af Power over Ethernet (PoE) support**  
simplifies deployment and dramatically reduces installation costs by helping to eliminate the time and cost involved in supplying local power at each access point location
- **Auto-MDIX**  
automatically adjusts for straight-through or crossover cables on all 10/100 ports

### Mobility

- **Anywhere, anytime wireless coverage**  
includes a single radio IEEE 802.11 a/b/g/n access point; per-radio software-selectable configuration of frequency bands; self-healing, self-optimizing local mesh that extends network availability; Wi-Fi Alliance Certification for interoperability with all IEEE 802.11 a/b/g/n client devices; and IEEE 802.3af PoE
- **Medical standards**  
meets the European EN60601-1-2 standard for healthcare
- **Interoperability**  
meets Wi-Fi Alliance Certifications, including IEEE 802.11g Wi-Fi and WPA2, to help ensure multivendor interoperability
- **Virtual Service Communities (VSCs)**  
includes up to 16 SSIDs, each with unique MAC address and configurable SSID broadcasts; individual security and QoS profiles per VSC; configurable DTIM and minimum data rate per VSC; VSCs that can be mapped to separate IEEE 802.1Q VLANs; WMM and/or WMM-PS; a security filter; and an IP filter
- **AP client access control functions**
  - IEEE 802.1X authentication using EAP-SIM, EAP-FAST, EAP-TLS, EAP-TTLS, and PEAP
  - MAC address authentication using local or RADIUS access lists
  - RADIUS AAA using EAP-MD5, PAP, CHAP, and MS-CHAPv2
  - RADIUS Client (RFC 2865 and 2866) with location-aware support
  - Layer 2 wireless client isolation

## Security

- **Integrated IDS support (Premium Mobility version required)**
  - **Automated AP and client classification**  
reduces manual effort (administrator can override AP classification)
  - **Comprehensive detection capabilities**  
detects a wide range of attacks
  - **Flexible event reporting**  
enables configuration of events that will result in notifications
  - **Location tracking capabilities**  
helps identify the location of the rogue device
  - **Flexible deployment models**  
supports time slicing or dedicating a radio to detect fulltime
- **IEEE 802.1X support**  
provides port-based user authentication with support for Extensible Authentication Protocol (EAP) MD5, TLS, TTLS, and PEAP with choice of AES, TKIP, and static or dynamic WEP encryption for protecting wireless traffic between authenticated clients and the access point
- **Choice of IEEE 802.11i, WPA2, or WPA**  
locks out unauthorized wireless access by authenticating users prior to granting network access; robust Advanced Encryption Standard (AES) or Temporal Key Integrity Protocol (TKIP) encryption secures the data integrity of wireless traffic
- **TKIP/WEP encryption**  
is supported only on legacy IEEE 802.11a/b/g clients as it has been deprecated from the IEEE 802.11n standard
- **Local wireless bridge client traffic filtering**  
when enabled, prevents communication between wireless devices associated with the same access point

## Additional information

- **RFC support**  
refer to the "Mobility Specification Sheet" for a list of RFCs and other industry standards supported by the MSM solution at <http://h17007.www1.hp.com/docs/mobility/4AA3-3883ENW.pdf>

## Warranty and support

- **Lifetime warranty**  
for as long as you own the product with advance replacement and next-business-day delivery (available in most countries)†
- **Electronic and telephone support**  
limited electronic and telephone support is available from HP; to reach our support centers, refer to [www.hp.com/networking/contact-support](http://www.hp.com/networking/contact-support); for details on the duration of support provided with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)
- **Software releases**  
to find software for your product, refer to [www.hp.com/networking/support](http://www.hp.com/networking/support); for details on the software releases available with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)

†HP warranty includes repair or replacement of hardware for as long as you own the product, with next business day advance replacement (available in most countries). The disk drive included with HP AllianceOne Advanced Services and Services z1 Modules, HP Threat Management Services z1 Module, HP AllianceOne Extended z1 Module with Riverbed Steelhead, HP MSM765z1 Mobility Controller and HP Survivable Branch Communication z1 Module powered by Microsoft Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at [www.hp.com/networking/warranty](http://www.hp.com/networking/warranty).

# HP MSM-802.11n Access Point Series

## Specifications



**HP MSM410 Access Point (US) (J9426B)**  
**HP MSM410 Access Point (JP) (J9529B)**  
**HP MSM410 Single Radio 802.11n AP (IL) (J9616A)**  
**HP MSM410 Access Point (WW) (J9427C)**

<b>Ports</b>	1 RJ-45 autosensing 10/100/1000 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 1 RJ-45 serial console port
<b>AP characteristics</b>	
Radios	Single (a/b/g/n)
Radio operation modes	Client access, Local mesh, Packet capture
AP operation modes	Autonomous and controlled
Wi-Fi Alliance Certification	a/b/g/n Wi-Fi Certified
<b>Physical characteristics</b>	
Weight	5.19(w) x 6.16(d) x 1.94(h) in (13.17 x 15.64 x 4.94 cm)
Enclosure	0.72 lb (0.33 kg) mounting bracket Indoor, plenum rated
<b>Memory and processor</b>	
Processor	Single core @ 384 MHz, 128 MB flash, 256 MB SDRAM
<b>Mounting</b>	Includes two mounting clips
<b>Environment</b>	
Operating temperature	32°F to 122°F (0°C to 50°C)
Operating relative humidity	5% to 95%, noncondensing
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
Nonoperating/Storage relative humidity	5% to 95%, noncondensing
<b>Electrical characteristics</b>	
Description	IEEE 802.3af PoE compliant for Gigabit Ethernet
Maximum power rating	8 W
Antenna	(3) Integrated, dual-band 2.4/5 GHz omnidirectional antennas
Number of internal antennas	3
<b>Frequency band and operating channels</b>	
FCC	2.412 - 2.462 GHz (1 - 11 channels) 5.180 - 5.240 GHz (36 - 48 channels) 5.260 - 5.320 GHz (52 - 64 channels) 5.500 - 5.700 GHz (100 - 140 (excluding 120, 124 and 128) channels) 5.745 - 5.825 GHz (149 - 165 channels)
European Union	2.412 - 2.472 GHz (1 - 13 channels) 5.180 - 5.240 GHz (36 - 48 channels)
Rest of World (Actual channels designated by selecting country in UI)	2.412 - 2.472 GHz (1 - 13 channels) 5.180 - 5.240 GHz (36 - 48 channels) 5.260 - 5.320 GHz (52 - 64 channels) 5.500 - 5.700 GHz (100 - 140 channels) 5.745 - 5.825 GHz (149 - 165 channels)
Taiwan	2.412 - 2.462 GHz (1 - 11 channels) 5.280 - 5.320 GHz (56 - 64 channels) 5.745 - 5.825 GHz (149 - 165 channels)
Japan	2.412 - 2.472 GHz (1 - 13 channels) 5.180 - 5.240 GHz (36 - 48 channels) 5.260 - 5.320 GHz (52 - 64 channels)
Israel	2.412 - 2.472 GHz (1 - 13 channels) 5.180 - 5.240 GHz (36 - 48 channels) 5.260 - 5.320 GHz (52 - 64 channels)
European Union (J9427B)	2.412 - 2.472 GHz (1 - 13 channels) 5.180 - 5.240 GHz (36 - 64 channels) 5.260 - 5.320 GHz (52 - 64 channels) 5.500 - 5.700 GHz (100 - 140 (excluding 5600-5650 MHz) channels)
<b>Radio</b>	FCC Part 15.247; FCC Part 15.407 (US); RSS-210 (Canada); EN 300 328; ARIB STD-T66; IDA Registration (Singapore); RCR STD-33; ARIB STD-T71 (Japan); EN 301 893 (EU); KCC approval (Korea)
<b>Safety</b>	UL 2043; UL 60950-1; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1
<b>Medical</b>	EN60601-1-2

# HP MSM-802.11n Access Point Series

## Specifications (continued)

**HP MSM410 Access Point (US) (J9426B)**  
**HP MSM410 Access Point (JP) (J9529B)**  
**HP MSM410 Single Radio 802.11n AP (IL) (J9616A)**  
**HP MSM410 Access Point (WW) (J9427C)**

<b>RF Exposure</b>	FCC Bulletin OET-65C; RSS-102; CFR 47, Part 2, Subpart J; ANSI/IEEE C95.1 (99); Ministry of Health Safety Code 6; Australian Radiation Protection Std.
<b>Features</b>	Single radio: IEEE 802.11n for high-throughput applications and IEEE 802.11a/b/g for legacy support - Integrated antennas for both IEEE 802.11a/b/g (diversity) and 802.11n (3x3 MIMO) - Will operate the radio at full power on IEEE 802.3af PoE for Gigabit Ethernet
<b>Emissions</b>	EN 55022 Class B; EN 301 489-1; EN 301 489-17; ICES-003 Class B; FCC Part 15, Class B
<b>Notes</b>	Maximum transmit power varies by country.
<b>Services</b>	3-year, 4-hour onsite, 13x5 coverage for hardware (UN683E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UN684E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UN686E) 3-year, 24x7 SW phone support, software updates (UN685E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR939E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR940E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR941E) 4-year, 4-hour onsite, 13x5 coverage for hardware (US013E) 4-year, 4-hour onsite, 24x7 coverage for hardware (US014E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (US015E) 4-year, 24x7 SW phone support, software updates (US016E) 5-year, 4-hour onsite, 13x5 coverage for hardware (US017E) 5-year, 4-hour onsite, 24x7 coverage for hardware (US018E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (US019E) 5-year, 24x7 SW phone support, software updates (US020E) 3 Yr 6 hr Call-to-Repair Onsite (UW416E) 4 Yr 6 hr Call-to-Repair Onsite (UW417E) 5 Yr 6 hr Call-to-Repair Onsite (UW418E) 1-year, 6 hour Call-To-Repair Onsite for hardware (HR943E) 1-year, 24x7 software phone support, software updates (HR942E) 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS830E) 1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS831E) 3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS832E) 3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS833E) 4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS834E) 4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS835E) 5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS836E) 5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS837E)
	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

# HP MSM-802.11n Access Point Series

## Specifications (continued)

---

HP MSM410 Access Point (US) (J9426B)  
HP MSM410 Access Point (JP) (J9529B)  
HP MSM410 Single Radio 802.11n AP (IL) (J9616A)  
HP MSM410 Access Point (WW) (J9427C)

---

### Radio characteristics:

HP MSM410 Access Point (US) (J9426B)  
HP MSM410 Access Point (JP) (J9529B)  
HP MSM410 Single Radio 802.11n AP (IL) (J9616A)  
HP MSM410 Access Point (WW) (J9427C)

Note: These radio characteristics apply to all the products in this series.

#### IEEE 802.11n 5 GHz @ 20 MHz

Data rate	MCS0/MCS8 Mbps	MCS7/MCS15 Mbps
Receiver sensitivity	-95 dBm	-77 dBm
Transmit power	18 dBm	10 dBm

#### IEEE 802.11n 5 GHz @ 40 MHz

Data rate	MCS0/MCS8 Mbps	MCS7/MCS15 Mbps
Receiver sensitivity	-92 dBm	-74 dBm
Transmit power	17 dBm	10 dBm

#### IEEE 802.11n 2.4 GHz @ 20 MHz

Data rate	MCS0/MCS8 Mbps	MCS7/MCS15 Mbps
Receiver sensitivity	-96 dBm	-79 dBm
Transmit power	19 dBm	10 dBm

#### IEEE 802.11n 2.4 GHz @ 40 MHz

Data rate	MCS0/MCS8 Mbps	MCS7/MCS15 Mbps
Receiver sensitivity	-91 dBm	-75 dBm
Transmit power	17 dBm	10 dBm

#### IEEE 802.11a

Data rate	6 Mbps	54 Mbps
Receiver sensitivity	-95 dBm	-82 dBm
Transmit power	18 dBm	12 dBm

#### IEEE 802.11b

Data rate	1 Mbps	11 Mbps
Receiver sensitivity	-96 dBm	-92 dBm
Transmit power	18.5 dBm	18.5 dBm

#### IEEE 802.11g

Data rate	6 Mbps	54 Mbps
Receiver sensitivity	-96 dBm	-83 dBm
Transmit power	18 dBm	13 dBm

---

# HP MSM-802.11n Access Point Series

## Specifications (continued)

---

HP MSM410 Access Point (US) (J9426B)  
 HP MSM410 Access Point (JP) (J9529B)  
 HP MSM410 Single Radio 802.11n AP (IL) (J9616A)  
 HP MSM410 Access Point (WW) (J9427C)

---

HP MSM410 Access Point (US) (J9426B)  
 HP MSM410 Access Point (JP) (J9529B)  
 HP MSM410 Single Radio 802.11n AP (IL) (J9616A)  
 HP MSM410 Access Point (WW) (J9427C)

MCS Index	800 nS Guard Interval		400 nS Guard Interval	
	20 MHz Rate (Mbps)	40 MHz Rate (Mbps)	20 MHz Rate (Mbps)	40 MHz Rate (Mbps)
0	6.5	13.5	7.2	15
1	13	27	14.4	30
2	19.5	40.5	21.7	45
3	26	54	28.9	60
4	39	81	43.3	90
5	52	108	57.8	120
6	58.5	121.5	65	135
7	65	135	72.2	150
8	13	27	14.4	30
9	26	54	28.9	60
10	39	81	43.3	90
11	52	108	57.8	120
12	78	162	86.7	180
13	104	216	115.6	240
14	117	243	130	270
15	130	270	144.4	300

---

**Standards and Protocols**

(applies to all products in series)

---

<b>Mobility</b>	IEEE 802.11a High Speed Physical Layer in the 5 GHz Band	IEEE 802.11b Higher-Speed Physical Layer Extension in the 2.4 GHz Band IEEE 802.11d Global Harmonization IEEE 802.11g Further Higher Data Rate Extension in the 2.4 GHz Band	IEEE 802.11i Medium Access Control (MAC) Security Enhancements IEEE 802.11n WLAN Enhancements for Higher Throughput
-----------------	--	--	--



## HP MSM-802.11n Access Point Series accessories

### Power Supply

HP 1-port Power Injector (J9407B)



HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.

---

**To learn more, visit [hp.com/networking](http://hp.com/networking)**

© Copyright 2009-2010, 2012-2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft is a U.S. registered trademark of Microsoft Corporation.

4AA2-9922ENW, Created October 2009; Updated July 2013, Rev. 4

